# OWENS CORNING ®

## SAFE USE INSTRUCTION SHEET

Creation Date 28-Aug-2018 Revision Date 19-Mar-2021 Version 2

#### 0. General Information

This Safe Use Instruction Sheet is the document provided by Owens Corning to communicate recommended safe handling and use instructions for manufactured articles neither regulated by OSHA Hazard Communication Standard, 29 CFR 1910.1200 nor by the Canada Hazardous Products Regulation SOR/2015-17 (WHMIS 2015)

#### 1. IDENTIFICATION

Product Name Self-Adhered Synthetic Underlayment

Synonyms Weatherlock® G. Weatherlock® Mat, Weatherlock® Flex, Weatherlock® Specialty Tile &

Metal, Titanium® PSU30, RhinoRoof® Granulated, RhnoRoof® High Temperature,

DeckSeal Low Sloop Roofing

Product code OCIW00009

Recommended Use Roofing underlayment with self-adhesive layer

Manufacturer Address Owens Corning

One Owens Corning Parkway

Toledo, OH 43659

Company Phone Number 1-800-GET-PINK or 1-800-438-7465

**24 Hour Emergency Phone Number** Chemtrec 1-800-424-9300 or 1-703-741-5970 CCN17393

**Emergency Telephone** 1-419-248-5330 (after 5 pm ET and weekends)

Company Website <a href="https://www.owenscorning.com/">https://www.owenscorning.com/</a>

## 2. HAZARDS IDENTIFICATION

#### **Regulatory Status**

This product is considered an article. 29 CFR 1910.1200(c) definition of an article is as follows: "Article" means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical (as determined under paragraph (d) of this section), and does not pose a physical hazard or health risk to employees

This product is considered an article per the Canadian Hazardous Products Regulation SOR/2015-17

Manufactured articles which meet the definition of the Canadian Hazardous Products Act (any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product) are not regulated by the Canadian Hazardous Products Regulation SOR/2015-17

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

\_\_\_\_\_

This product is considered as an article. No hazardous components are included in this product.

## 4. FIRST AID MEASURES

#### **Description of First Aid Measures**

Eye contact
Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a physician

**Skin contact** • Wash skin thoroughly with soap and water

**Inhalation** • Remove to fresh air

Ingestion • Clean mouth with water and drink afterwards plenty of water

## 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media • Use extinguishing agent suitable for type of surrounding fire

Protective equipment and precautions for firefighters

• As in any fire, wear self-contained breathing apparatus (positive-pressure), MSHA/NIOSH

(approved or equivalent) and full protective gear

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions • Avoid contact with eyes and skin

• Use personal protective equipment as required

Methods for cleaning up • Pick up and transfer to properly labeled containers

## 7. HANDLING AND STORAGE

Precautions for safe handling • Handle in accordance with good industrial hygiene and safety practice

Storage Conditions • Keep in a dry place

Incompatible materials • None known based on information supplied

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH REL
Petroleum Asphalt (non-paving use)	TWA: 0.5 mg/m³ benzene-soluble	0.5 mg/m³ Respirable/inhalable	Ceiling: 5 mg/m <sup>3</sup> fume 15 min
8052-42-4	aerosol fume, inhalable particulate	fraction	
	matter		
Continuous filament glass fiber,	TWA: 1 fiber/cm3 respirable fibers:	-	-
non-respirable	length >5 µm, diameter less than 3		
65997-17-3	μm, aspect ratio >=3:1, as		
	determined by the membrane filter		
	method at 400-450X magnification		
	[4-mm objective], using		
	phase-contrast illumination		
	TWA: 5 mg/m³ inhalable particulate		
	matter		

NIOSH REL Immediately Dangerous to Life or Health

\* The chemical/substance is well embedded in the final product and will not be exposed to under normal condition.

Engineering Controls Eyewash stations

Individual protection measures, such as personal protective equipment

**Eye/face protection** • Wear safety glasses with side shields (or goggles)

Skin and body protection • Wear protective gloves

· Wear long-sleeved shirt and long pants

Respiratory protection • If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations

General Hygiene Considerations • Handle in accordance with good industrial hygiene and safety practice

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Solid

Odor Slight petroleum Color various

Water solubility Insoluble in water

#### 10. STABILITY AND REACTIVITY

Possibility of Hazardous Reactions • None under normal processing conditions

Hazardous Decomposition Products • None known based on information supplied

#### 11. TOXICOLOGICAL INFORMATION

Product Information No data available

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

Disposal should be in accordance with applicable regional, national and local laws and regulations

#### 14. TRANSPORT INFORMATION

This material is not subject to regulation as a hazardous material for shipping

## 15. REGULATORY INFORMATION

International Inventories This product is classified as an article. Articles are exempted from registration or listing

under chemicals inventories like TSCA (USA), DSL/NDSL (CAN), REACH (EU), ENCS (JP), IECSC (CN), KECL (KR), PICCS (PH), AICS (AUS)



This product can expose you to chemicals including those listed below, which is [are] known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www P65Warnings ca gov

For more information go to www.Foowaniings.ca.gov		
Chemical name	California Proposition 65	
Bitumen, extracts of steam-refined and air refined 9999-99-9	CARCINOGEN	

## **16. OTHER INFORMATION**

Creation Date28-Aug-2018Revision Date19-Mar-2021

Revision Note No information available

#### **Disclaimer**

The information provided in this Safe User Instruction Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safe Use Instruction Sheet**